

TECHNICAL DATA

CARE AND READING LIGHTS

FITTED WITH	1 x LED lamp - D68798000
LUMINOUS POWER	1 000 Lux / 0,5 m 1 000 Lux / 0,5 m
ILLUMINANCEFIELD 0,5 M	Ø 45 cm
COLOR RENDERING INDEX (CRI)	> 80
COLOUR TEMPERATUR	approx. 3000 K
WORK EQUIPMENT	electronic plug-in transformer
CONNECTED LOAD	100-240 V; 50/60 Hz
MAINS LEAD	2 m Euro
LUMINAIRE BODY	PC / aluminium, painted
WEIGHT (NET)	approx. 1.5 kg
POWER CONSUMPTION	approx. 9 W
BALANCE OF ARTICULATION JOINTS	friction
CLASS OF PROTECTION	II
ACCESSORY	universal bedside adapter with roll-out protection, light decor foil, light decor rattan, light decor white, rail fastening with removal protection, table clamp with removal protection, universal fastening with removal protection, wall bracket with removal protection
NORMS	EN 60598-1, EN 60598-2-25
SPECIAL FEATURES	night light LED
FASTENING	rail, table, wall, pin (16 mm W)
ORDER NUMBER	D15250000 - white aluminium



LIGHT DISTRIBUTION

TECHNICAL DRAWING

measuring distance 0.5 m

