

Dmed® halux LED 20-1 P FX

TECHNICAL DATA

EXAMINATION LIGHTS

FITTED WITH	1 x LED lamp - D68775000
LUMINOUS POWER	40 000 Lux / 0.5 m
ILLUMINANCEFIELD0,5 M	Ø 17 cm
COLOR RENDERING INDEX (CRI)	> 93
COLOUR TEMPERATUR	approx. 4400 K
WORK EQUIPMENT	electronic converter
CONNECTED LOAD	220-240V; 50/60Hz
MAINS LEAD	1,8 m
LUMINAIRE BODY	polycarbonate (PC)
POWER CONSUMPTION	approx. 13 W
USAGE	rocker switch (I/O) at the arm
BALANCE OF ARTICULATION JOINTS	spring
CLASS OF PROTECTION	II
ACCESSORY	roll support, rail fastening with removal protection, table clamp with removal protection, universal fastening with removal protection, extension arm with removal protection, wall bracket with removal protection
NORMS	EN 60601-1, EN 60601-2-41
SPECIAL FEATURES	switchable, maintenance free
FASTENING	rail, table, wall
ORDER NUMBER	D15472000 - pure white



LIGHT DISTRIBUTION

TECHNICAL DRAWING

measuring distance 0.5 m

