

# Dmed® triango 30 F

## TECHNICAL DATA

## TREATMENT LIGHTS

FITTED WITH	1 x LED lamp
LUMINOUS POWER	60'000 Lux / 1,0 m
ILLUMINANCEFIELD 1,0 M	Ø 16 cm
COLOR RENDERING INDEX (CRI)	> 95
COLOUR TEMPERATUR	approx. 4500 K
DEPTH OF ILLUMINATION L1+L2	1.2 m
WORK EQUIPMENT	electronic converter
CONNECTED LOAD	100-240 V; 50/60 Hz
MAINS LEAD	3 m Schuko
LUMINAIRE BODY	polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)
WEIGHT (NET)	approx. 20.0 kg
POWER CONSUMPTION	approx. 30 W
BALANCE OF ARTICULATION JOINTS	spring (weight compensation)
CLASS OF PROTECTION	I
ACCESSORY	sterilizable handle
NORMS	EN 60601-1, EN 60601-2-41
SPECIAL FEATURES	sterilisable grip, continuously dimmable, maintenance free
FASTENING	roller stand
SYSTEM OF PROTECTION	IP 43
ORDER NUMBER	D15171000 - pure white



## LIGHT DISTRIBUTION

## TECHNICAL DRAWING

